



QPCA09YZMW

Portable Air Conditioner

\$369 MSRP



Dimensions (HxWxD)

24 3/4" x 15 1/4" x 14"



Manuals

<u>Installation Instructions</u>
<u>Use and Care Manual</u>

Product Features

Room Size

3-IN-1
Portable Air
Conditioner

Auto Evaporation Technology **Dehumidify**

Delivers 8,500 ASHRAE (5,600 SACC) BTUs to cool MEDIUM rooms up to 250 sq ft With built-in air conditioning, fan modes and dehumidifying capability for flexibile & optimal home comfort

Evaporates the water under most room conditions with no bucket to empty

Dehumidify
mode
optimizes
moisture
removal with
minimal cooling

Digital Thermostat

Easy to operate controls with a digital thermostat

24 Hour Timer

24 Hour Timer -Set the timer for continuous cool

Remote Control

Easy to operate digital controls with remote control

Install

Installation kit included

Window Size

Single hose exhaust for double hung & sliding windows types. Fits windows 20"- 46" wide, minimum height 4.8"

Specs & Details

Capacity	
Cooling BTUH (MAX)	8500.0 Btu
Dehumidification (pts./day)	55.0 pt

Features	
Plug Capacity	120V/13A
Control Type	Tactile, Variable LED Display with Nightlight
Fan Speed Selections	3 Cooling, 3 Fan Only
Power Cord Length	6'
Operating Temperature Range F	60-86
Product Type	Portable
Refrigerant Type	R-410A
Exhaust Hose Length	5.0 ft

Appearance	
Easy-Roll Casters	Yes
Installation	Extended Length Window Kit - 48"
Color Appearance	White

Weights & Dimensions	
Overall Width	15.25 in
Approximate Shipping Weight	66.0 lb
Min./Max. Window Opening Width (in.)	20/46
Overall Height	24.75 in
Minimum Window Opening Height (in.)	4.75
Overall Depth	14.0 in
Net Weight	52.0 lb

Power / Rating	s

Filter Type	Easy Access, Permanent Mesh
Condensate Drain	Self-Evaporative
Vent/Air Exchange Exhaust	Тор
Plug Type	A / 5-15P
Unit Features	Auto Restart, Dehumidify Function
Remote Control	Yes
Thermostat Type	Thermistor
LCDI / AFCI power cord	Yes
EER	6.4
Airflow (cfm) Roomside (hi/low)	175/155/135
Digital Time Temp Display	Yes
Window Exhaust Kit	Yes
Room Air Conditioner Features	24 Hr. Timer
Airflow	Single-hose

Volts/Hertz	115V
Cooling - Rated Cooling Amps AHAM	7.5
Cooling - Watts	860

Configuration

Claims & Certifications	
ASHRAE 128	Yes
CUL	Yes
California Prop 65	Yes
Rohs Compliant	Yes
UL	Yes

Support



Product FAQs

See our frequently asked (and answered) questions.



Schedule Service

You can schedule a service call 24 hours a day with our easy-to-use online form.



Parts & Accessories

Order
accessories
and repair parts
from our parts
store.



Contact Us

Still have questions? We've got your back. Chat, email, or give us a call.